

ECOPROTECT™ & ECOCLEAN™ Surface Protection Films



Films for all surfaces!

- ✓ Aluminium Composite Panels
- ✓ Aluminium & uPVC Profiles
- ✓ Stainless Steel
- ✓ Marble, Stone, Quartz
- ✓ Pre-Coated Metals
- ✓ Window & Glass
- ✓ Decorative Laminates
- ✓ HVAC/Vent/Duct
- ✓ Home & Automotive Carpets
- ✓ Plastic Sheets

75

Million
Square Meters

Surface Protection Films - Annual Capacity


Ecoplast Ltd.


Ecoplast Ltd.

1 4+ Decades of
Manufacturing
Experience

2 Public Company
- Listed on the
Bombay Stock
Exchange

3 ISO 9001,
14001, 22000
Certified

4 Start-of-the-
art Automated
Facility

ECOPROTECT™ Surface Protection Films

for White Goods &
Domestic Appliances



Trusted and
innovative
suppliers of
Surface
Protection Films

@ www.ecoplastindia.com | +91- 22-66664050
📧 info@ecoplastindia.com | +91- 22-68324115

Sales Office: 1309/1310 Hubtown Solaris, N.S. Phadke
Road, Andheri E, Mumbai, Maharashtra, India - 400069

Works & Reg. Office: N.H. No. 8, Waterworks Cross
Road, Abrama, Valsad, Gujarat, India - 396 002

ECOPROTECT™

Surface Protection Films

for White Goods & Domestic Appliances

ECOPROTECT™ is a series of Surface Protection Films designed specifically for the protection of White Goods & Domestic Appliances.

There are numerous risks of damage, scratches, and contamination throughout the production, storage, transit, and installation phases of your materials.

Our engineered protective films are tailored to preserve the integrity of your product's surface.



Refrigerators

Compatible with Special Coatings

HEAT
RESISTANT
COATING


FINGERPRINT
RESISTANT
COATING



Washing Machine

Easy Peel

- Notable innovation with a special formulation
- Easy Peel films are quick & effortless to remove



Faster you peel or remove, the easier it gets to peel off (less force required)

KEY FEATURES



Easy, uniform, and quiet unwinding of film rolls.



Customized for each application and its relevant properties / processes for optimal adhesion



Film does not lift or get removed during high mechanical stress operations such as Bending, Punching, and Folding.



Films have ideal puncture resistance, tensile strength, and elongation properties. No fibers or strains visible after cutting



Transparent & highly aesthetic films give a premium aspect to the product and allow for thorough visual control during production.



Zero risk of any residue (film or adhesive) left behind on the profile surface

FEATURED PRODUCTS & TECHNICAL DATA

Product	ECOPROTECT™ 207G-X	ECOPROTECT™ 208G-X
Common Thickness (mic)	50	50
Common Colour	Clear Transparent	Clear Transparent
Adhesive Type	Water Acrylic	Water Acrylic
Tensile Strength (gms/mm ²) - MD	16 - 18	16 - 18
Tensile Strength (gms/mm ²) - TD	17 - 19	18 - 20
Elongation (%) - MD	200 - 300	250 - 350
Elongation (%) - TD	500 - 600	550 - 650
Adhesion Value (gms/25mm)	70 - 140	90 - 150

Designed for all End Applications



Oven



Air Conditioner



Dishwasher

Dryer

Freezer

Cooker & Toaster

Mixer & Grinder

